



2024-07-30 | D0497959

No rights whatsoever can be derived from the shown image(s)

Detailed Specification

Cab exterior	<ul style="list-style-type: none"> - Reinforced mechanical cab suspension. - Bumper mounted light units with combined fog light and cornering light function. - Central door lock system with exterior light check function. Includes 2 remote control units and 3 transponder keys. - 3 - Bi-reflector halogen head lights with impact-resistant Lexan lens. - Preparations for the installation of an external sun visor. - Head light beam for left-hand traffic. - Daytime running lights. - Green tinted glass. - Main mirror and wide angle mirror at driver's side and co-driver's side. Kerb view mirror at co-driver's side. - Mirror brackets for body width 2.50 - 2.60 m. - Front view mirror to comply with EC directive 2003/97/EC for frontal field of view.
Colours	<ul style="list-style-type: none"> - Chassis colour black. - Cab colour: H3279WHITE - Colour of the headlamp panel and the bumper: Stone Grey. - Cab steps and wing Stone Grey.
Cab interior	<ul style="list-style-type: none"> - Steering wheel, finished with leather in black colour. - Luxury air suspended driver seat with adjustable damper and pneumatic lumbar support. Seat cushion heating. Integral head restraint. Three-point seat belt. Seat upholstery velour. - Arm rest on the driver seat. - Seat belts in colour red, to enable a visual seat belt check from outside the cab. - Manually controlled airco with air recirculation. - Air suspended co-driver seat with integral head restraint and three-point seat belt. Seat upholstery velour with vinyl rear. - Adjustable arm rest at the inner side of the co-driver seat. - Right-hand drive. - Steering column rake adjustment with mechanical lock. - Storage box on the engine tunnel. - Electric window openers. - Converter 24V to 12V, 15A, 180W.
Communication and driving management	<ul style="list-style-type: none"> - Speed limiter setting 85 km/h nominal. The tolerance enables a maximum vehicle speed of 88.5 km/h. - PACCAR Connect is an online fleet management system giving insight in relevant truck, driver and location information. - Digital (smart) tachograph Stoneridge SE5000 Connekt with Global Navigation Satellite System (GNSS) receiver and Dedicated short-range communications (DSRC) unit, compliant to EU Mobility package 1 as described in the EU tachograph regulations. - Speedometer with main scale in m/h and secondary scale in km/h. - Speaker system with 2 speakers. - Combi-antenna for AM/FM, GSM and GPS. GSM ranges 900 MHz, 1800 MHz and GPRS. - Driver Performance Assistant (DPA). Interactive programme to support the driver in achieving the most cost effective driving style. The DPA information is shown on the 5 inch full colour TFT display in the instrument panel.

Detailed Specification

Safety and security	<ul style="list-style-type: none"> - Broadband reverse warning with self-adjusting volume. - Lane Departure Warning System to prevent inadvertent lane changes due to driver's fatigue or distraction and to form an effective driving aid in low visibility conditions. - Electronic Vehicle Stability Control system (VSC) to enhance the active driving safety. Improved directional stability (understeer, oversteer jack-knifing) and additional roll-over safety.
Suspension and axles	<ul style="list-style-type: none"> - Single reduction driven rear axle type SR5.14 with electronically controlled 2-bellow air suspension, including shock absorbers and stabiliser. Max. load 5.00 tonnes. - Front axle type F36. Parabolic leaf suspension with shock absorbers and stabiliser. Max. load 3.6 tonnes.
Wheels and tyres	<ul style="list-style-type: none"> - Front axle(s): tyre size 215/75R17.5, wheel size 17.5 x 6.00. - Driven rear axle(s): tyre size 215/75R17.5, wheel size 17.5 x 6.00. - Supplier Goodyear. - Tyre Pressure Indication system. The system monitors speed differences between the wheels. Tyre pressure warnings are given on the LCD display in the instrument panel. - Steel disc wheels, silvergrey. - Wheel protection rings with open centre section, colour silver-grey (RAL 9006). - Spare wheel tyre not applicable.
Driveline	<ul style="list-style-type: none"> - Driven rear axle with a mechanical differential lock. - Rear axle ratio 3.31. - Engine PX-5, 4 cylinder diesel engine, 4.5 litres. Output 153 kW (208 hp) at 2300 rpm. Max. torque 795 Nm at 1300-1600 rpm. - Automatic overdrive gearbox PowerLine 8AP800, ratio 4.89-0.64, 8 speeds. - Automatic gearbox PowerLine, 8-speeds. - Exhaust emission Euro 6. - Engine idle shutdown, after idling 5 minutes. - The ASR (anti-slip regulation) system prevents the driven wheels from slipping when accelerating at driving off and helps the vehicle to remain stable on critical road surfaces. - On-board diagnostics (OBD) system compliant with Euro VI Step E requirements.
Brake system	<ul style="list-style-type: none"> - Park brake control with spoken park brake warning. - Exhaust brake. Function integration in the Electronic Brake System. If switched on with the steering wheel switch, the exhaust brake will operate on throttle release.
Chassis	<ul style="list-style-type: none"> - Plastic fuel tanks 2x 155 litres. - Rear light unit with LEDs. - Front underrun protection (FUP), according to EU directive 2000/40/EEC. - Wheelbase 5.40 m / rear overhang 2.43 m. - Rear light brackets. - Side member height 210 mm, thickness 4.5 mm. No inner reinforcement. - Standard location of chassis components. - EAS unit and rearward exhaust discharge at the right-hand side of the chassis. - Battery box at the left-hand side. No spare wheel carrier. - Fuel tank at the left-hand side of the chassis.

Detailed Specification

	<ul style="list-style-type: none"> - 30 litres tank for AdBlue® positioned at the right-hand side of the chassis. - Filler cap without lock for tank for AdBlue®. - Spray suppression in the mudguards, according to directive 91/226/EEC.
Drawbar and trailer equipment	<ul style="list-style-type: none"> - Type plate related solo application, without trailer. - Closing cross member.
Bodies and preparations for bodying	<ul style="list-style-type: none"> - Hardwired body signals and warnings. - Application connector for tail lift control on the chassis (A088). Electric signals for -Cab tilt locked- and -Engine running-. Power supply 24 V after contact. Spare wiring to the dashboard. Includes dashboard indications for -Taillift control active- and - Tail lift down- and a signal for engine starter inhibit with tail lift not closed. - Body attachment BAM 1, with consoles type B - loose items supply. As of production week 2019-45 the first console (nearest to the cab) will be pre-mounted on either side of the chassis. - Loose supply of a wiring loom with LED-type side marker lights. - Chassis frame prepared for standard applications.
24V power supply	<ul style="list-style-type: none"> - Alternator 100 A, batteries 2x 175 Ah.
GVM and GCM	<ul style="list-style-type: none"> - Chassis weight related technical GVM max. 7500 kg. - Driveline related technical GCM equal to GVM.
Application conditions	<ul style="list-style-type: none"> - Moisture separator with 30 micron filter element and heated filter bowl. Status panel with drain warning on the dashboard. - Air intake high behind cab. - Application class 10 comprises United Kingdom and Ireland. - Standard noise level. - Maximum ambient temperature 38 degrees.
Service and maintenance	<ul style="list-style-type: none"> - Warranty Plus - 3 Year Vehicle & 3 Year Driveline - takes care of all warrantable repairs on the vehicle and driveline for three years together with associated breakdown coverage. - DAF 2 Year Maintenance Package - takes care of all necessary planned maintenance requirements, safety and legal inspections excluding tachograph recalibration, MOT preparation, presentation and fees. To a maximum distance of 320,000 km. - Standard Warranty takes care of 1 year complete vehicle as supplied by the OEM (excl. real wear parts), 2nd year driveline and 1st year breakdown. - ITS service. - Delivery charge United Kingdom.
Vehicle delivery	<ul style="list-style-type: none"> - Vehicle delivery with 30 liters extra fuel. - Type plate EEC. - Whole Vehicle Type Approval (WVTA) for European Union.
Customer needs	







