

Summarized Specification XB 170 FA 4X2 Rigid, 08t air

Vehicle Summary

Rear axle ratio	Rear axle ratio 3.73
Gearbox execution	Automatic gearbox PowerLine, 8-speed
Cab colour	E1980WHTE
Roof air deflector	No roof air deflector
Fuel tank	Plastic fuel tank 185 l
Engine	Engine PX-5 , 124 kW/169 hp. Cab Badge: 170
Wheelbase / rear overhang	Wheelbase 3.90 m / rear overhang 2.23 m
Rear axle	Rear: 5.00 t, air suspension, SR5.13
Market packages	No market package
Application packages 1	No application option
Cab version	Day Cab
Connected Services	PACCAR Connect
Audio and infotainment	FM/DAB/DAB+ radio with speakers incl. phone con.
Front axle	Front: 3.60 t, parabolic, 36N
Supplier tyres	Goodyear
Tyres fr1 or fr axles	F1,215/75R17.5GO KMAXS2 128/126 M Steering CCA 3P
Tyres driven rear axle(s)	R1,215/75R17.5GO KMAXD2 128/126 M Traction CCA 3P
Spare tyre	SP, not applicable
Exhaust emission	Exhaust emission Euro 6
Chassis component layout	Standard component location
Tank for AdBlue® position and content	Tank for AdBlue® 30 l, right-hand side chassis
Type plate related drawbar or solo application	Type plate related solo application, no trailer
Body type	No ex works body type
Chassis weight related gross vehicle mass GVM	Chassis weight related technical GVM max 7500 kg
Vehicle warranty	Standard Warranty - 1Y Full - 2nd year DL - 1Y BD

Factory options

Cab exterior	
Bumper mounted fog lights.	
Bi-reflector halogen head lights with impact-resistant Lexan lens.	
Central door lock system with exterior light check function. Includes 2 remote control units and 3 transponder keys.	
3	
Cab interior	
Steering wheel, finished with leather in black colour.	
Luxury air suspended driver seat with adjustable damper and pneumatic lumbar support. Seat cushion heating. Integral head restraint. Three-point seat belt. Seat upholstery velour.	
Arm rest on the driver seat.	
Luxury dual mate seat with velour upholstery. Inner seat with folding backrest and armrest. Head rest and three-point seat belt for both the inner and the outer seat. Lockable storage space under the outer seat cushion.	
Adjustable arm rest at the inner side of the co-driver seat.	
No storage on engine tunnel	
ECAS remote control to activate normal driving height, to raise/lower the rear axle and to stop any adjustment.	
Communication and driving management	
Digital (smart) tachograph VDO DTDO with Global Navigation Satellite System (GNSS) receiver and Dedicated short-range communications (DSRC) unit, compliant to EU Mobility package 1 as described in the EU tachograph regulations.	
Suspension and axles	
Front axle 1, 3600 kg, tyre load index 128	
Single reduction driven rear axle type SR5.13 with electronically controlled 2-bellow air suspension, including shock absorbers and stabiliser. Max. load 5.00 tonnes.	

Driveline		
Rear axle ratio 3.73.		
Driven rear axle with a mechanical differential lock.		
Engine PX-5, 4 cylinder diesel engine, 4.5 litres. Output 124 kW (169 hp) at 2300 rpm. Max. torque 695 Nm at 1100-1700 rpm.		
Brake system		
Park brake control with spoken park brake warning.		
Chassis		
Rear light unit with LEDs.		
Front underrun protection (FUP), according to EU directive 2000/40/EEC.		
Plastic fuel tank 185 litres.		
Rear underrun protection.		
Wheelbase 3.90 m / rear overhang 2.23 m.		
Rear light brackets.		
Bodies and preparations for bodying		
Hardwired body signals and warnings.		
24V power supply		
Alternator 100 A, batteries 2x 175 Ah.		
Application conditions		
Moisture separator with 30 micron filter element and heated filter bowl. Status panel with drain warning on the dashboard.		
Service and maintenance		
Delete DAF 2 year Preventive Maintenance - 320k.		
Warranty Plus - 3 Year Vehicle & 3 Year Driveline - takes care of all warrantable repairs on the vehicle and driveline for three years together with associated breakdown coverage.		
Customer needs		
General haulage		